

- Best Design!
- Excellent Quality!
- Outstanding Capability!

PEBCO COMNET 8850-L

Seize the Spotlight!

Pardakht Electronic Behestan Co. (**PEBCO Electronics**) provides the most reliable, versatile and cost effective models. Our next generation cash dispenser, the PEBCO-COMNET 8850-L in partnership with South Korea Chungho comnet Co. is designed to create efficient self service with fully advanced functions. It has bright features, outstanding capabilities and excellent qualithes. The PEBCO-COMNET 8850-L is now in the center stage as a new feature of global business.



Reliability

Designed with key technology and deep understanding of our customers' needs, the PEBCO-COMNET 8850-L can offer outstanding quality standards and reputation for exellent value.

Security

With its UL291 level 1 cabinet, PCI Certified EPP, security camera and anti-Skimming EMV card reader, the PEBCO-COMNET 8850-L is equipped for the highest level protection.

High Capacity

The PEBCO-COMNET 8850-L manages large capacities of cassettes and high transactions volumes. It is configured with 4 denominations with capacities for up to 3,000 notes for each cassette.

Customization

Our PEBCO-COMNET 8850-L Series technology can support future compliance and application needs in the banking industry by offering various options based on customers' specific needs.

PEBCO COMNET 8850-L



Specification

CUSTOMER HANDLING

Display	15.0" TFT Color LCD with 8 Metal Function Keys (Resolution 1024 x 768)
Keyboard	Encryption Pin Pad (4 x 4 numeric keys) with PCI 2.X Compliant
Card Reader	Motorized Card Reader (EMV, PBOC, Approved)

CONTROL UNIT & SYSTEM

CPU	Dual Core, 3.10 GHz
Memory	DDR3 2G
Storage	500G SATA HDD
Media	DVD - ROM
OS	Windows Pos Ready
Interface	TCP/IP (LAN) or Optional Dial-up Modem, Wireless

CASH DISPENSING

Cassette Capacity	3.000 Notes per Cassette
Number of Cassette	Up to 4 Cassette
Type	Present Type
Speed	7 notes / sec
Reject Box	Capacity Approx 300 Bills

RECEIPT PRINTER

Method	Direct Thermal Line Printer
Paper Setting	Semi-auto loading method

JOURNAL PRINTER

Method	Direct Thermal Line Printer
Paper Setting	Semi-auto loading method

SECURITY

Cabinet	UL 291 Level-1, GBA Compliant
Lock	Electric Lock, Long Key Lock

PHYSICAL

Maintenance Access	Front / Rear Access
Dimension (WxHxD)	506 x 1433 x 845 (mm)
Weight	Approx. 450 kg, 4-cartridge CDU, including options, bill & media

OPERATING ENVIRONMENT

Temperature	Indoor 10~32°C / TTW 0~40°C
Humidity	20~85%
Power Supply	AC100 - 240V, 50/60Hz

APPLICATION SOFTWARE

CEN/XFS Support	
NDC Support	
DDC Support	

INSTALLED ADDITIONAL PART

Bar Code (1D)	
Camera (Face, Hand)	

Head Office: PEBCO Building, No. 19, Mohebi St., Northern Sohrevardi Ave.,
 Tehran - IRAN +98 21 8817 3000
Factory: 19th St., Maadiran Sq., Hashtgerd Ind. Zone, Hashtgerd, Karaj - IRAN
www.brg-pebco.com info@brg-pebco.com