# Check Scanner WISESCAN200



#### Best Design!

- Excellent Quality!
- Outstanding Capability!

#### Seize the Spotlight

PEBCO, Manufacturer and supplier of various devices and machines with delegation Wise Cube from South Korea, presents the newest WiseScan check scanners (with collaboration with Hantel) with the purpose of increasing effectiveness and simplifying bank procedures. It has been designed reliably and based on best technologies and deep understanding of customer's needs.

#### **Key features:**


- · Capability of scanning both sides of check
- Receiving MICR information of check
- Printing needed information on the back of the check (Endorsement)
- Capability of fast scan
- High precision in reading codes
- · Capability of scanning conforming to standards
- Easy use and quiet operations


#### **General features:**

- Small dimensions: 155\*319\*175 (mm)
- Light weight (2.8 Kg)
- · Conformation with banking system of the country
- · Conformation with central bank (Markazi)standards
- · Conformation with international standards
- · Easy installation and use
- Reading embossing stamps

## wisecube

### WISESCAN200





#### Specification

Documents	The second s
Heights	54~106mm
Length	80~235mm
Weight	60~120g/m2
Scanner	and the second s
Scanning Side	Duplex
Sensor	CIS( Contact Image Sensor)
Scan Width	104mm
Resolution	100/200dpi
Color	Shit Grey, 1bit B/W, 24bit True Color
Image Formats	TIFF G4, JPEG, BMP
Processing Speed	Max. 90 dpm(180 ipm) with 6inch check
Printer	
Тура	Inkjet 12pin
Print Sequence	Printer before Scanning
Print Side	Rear Side
Estimated Yield	5~7M characters
Cartridge	HP C6602A
MICR Reader	
Recognize Codes	E13B and CMC7
Read Head	Magnetic head with permanent magnet excitation
nterface	and the second se
Type	USB 2.0 High Speed (480Mbps)
Physical Dimensions	
Size	155 x 319 x 175 (mm)
Neight	2.8 Kg
Pawer	and the second se
Adapter Input	AC 100~240V, 50~60Hz, 1.75A
Adapter Output	DC 24V/1.75A
Environment	and the second se
Operating Temperature	10-40°C
Operating Humidity	10 ~ 85%, Non condensing



